





CODE (Code)	2510320150CP
DI (Ø Diameter / mm)	32
TP (Type)	Centre distance to ISO, male rod
VE (Version)	Double-acting, through-rod
EX (Execution)	Standard
HUB (Stroke)	150
HUBST (Rod position)	0
MAT (Material)	C45 chromed rod
SE (Seal)	Polyurethane
AC1 (Front accessories)	
AC2 (Rear accessories)	
AC3 (Intermediate accessories)	
AC4 (Left sensors)	
AC5 (Right sensors)	
INFO (Catalogue)	Catalogue
A (/ mm)	47
B (/ mm)	32.5
B1 (/ mm)	
B2 (/ mm)	
B3 (/ mm)	
C (ØC / mm)	12
C1 (ØC1 / mm)	
CH (/ mm)	10
CH1 (/ mm)	17
D (/ mm)	48.5
E (ØE H9 / mm)	
F (/ mm)	
G (/ mm)	44.5
H (/ mm)	7.5
H1 (/ mm)	37
L (/ mm)	4
N (/ mm)	50.5
N1 (/ mm)	
N2 (/ mm)	56.5
O (Thread)	M6
O1 (ØO1 / mm)	5.2
P1 (Thread)	
P2 (/ mm)	
Q (Thread)	G1/8
R (Thread)	M10x1.25
S (/ mm)	22
S1 (/ mm)	

Stückliste

N°	Isim	Amount
1	2510320150CP	1