

## Nominal data

<b>Type</b>	A4D420-AP02-01		
<b>Motor</b>	M4D074-GA		
Phase		3~	3~
Nominal voltage	VAC	400	400
Connection		Y	Y
Frequency	Hz	50	60
Type of data definition		fa	fa
Valid for approval / standard		CE	CE
Speed	min <sup>-1</sup>	1430	1660
Power input	W	160	235
Current draw	A	0.44	0.45
Max. back pressure	Pa	160	120
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	65	40

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit  
Subject to alterations

## Data according to ErP directive

Installation category	A
Efficiency category	Static
Variable speed drive	No
Specific ratio*	1.00

\* Specific ratio =  $1 + p_{fs} / 100\,000\text{ Pa}$

		Actual	Request 2013	Request 2015
Overall efficiency $\eta_{es}$		34.5	25.5	29.5
Efficiency grade N		45	36	40
Power input $P_e$	kW	0.22		
Air flow $q_v$	m <sup>3</sup> /h	3540		
Pressure increase $p_{fs}$	Pa	81		
Speed n	min <sup>-1</sup>	1395		

Data established at point of optimum efficiency



A4D420-AP02-01

# AC axial fan

sickled blades (S series)

## Technical features

Mass	4.8 kg
Size	420 mm
Surface of rotor	Coated in black
Material of blades	Sheet steel, coated in black
Number of blades	5
Direction of air flow	"V"
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 44
Insulation class	"B"
Humidity class	F1-2
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensate discharge holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	< 0.75 mA
Cable exit	Variable
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60335-1
Approval	CCC




A4D420-AP02-01

# AC axial fan

sickled blades (S series)


## Product drawing



- |   |   |
|---|---|
| 1 | Connection line PVC 7G 0.5 mm <sup>2</sup> , 7x brass lead tips crimped |
| 2 | Direction of air flow "V"   |
| 3 | Depth of screw max. 10 mm   |




## Connection screen



Note: Direction of rotation changes when two phases are reversed

Δ	Delta connection	Y	Star connection	L1	black
L2	blue	L3	brown	U1	black
V1	blue	W1	brown	U2	green
V2	white	W2	yellow	PE	green/yellow

## Charts: Air flow 50 Hz



Measurement: LU-29817


Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: L<sub>wA</sub> measured as per ISO 13347 / L<sub>pA</sub> measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

	U	f	n	P <sub>e</sub>	I	qv	P <sub>fs</sub>
	V	Hz	min <sup>-1</sup>	W	A	m³/h	Pa
1	400	50	1430	160	0.44	4890	0
2	400	50	1420	188	0.48	4435	35
3	400	50	1400	218	0.51	3805	70
4	400	50	1375	256	0.55	2700	110

U = Supply voltage · f = Frequency · n = Speed · P<sub>e</sub> = Power input · I = Current draw · qv = Air flow · p<sub>fs</sub> = Pressure increase

## Charts: Air flow 60 Hz



Measurement: LU-29818

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: L<sub>wA</sub> measured as per ISO 13347 / L<sub>pA</sub> measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

	U	f	n	P <sub>e</sub>	I	qv	p <sub>fs</sub>
	V	Hz	min <sup>-1</sup>	W	A	m³/h	Pa
1	400	60	1660	235	0.45	5635	0
2	400	60	1635	271	0.52	5145	40
3	400	60	1595	315	0.57	4495	80
4	400	60	1550	365	0.65	3560	120

U = Supply voltage · f = Frequency · n = Speed · P<sub>e</sub> = Power input · I = Current draw · qv = Air flow · p<sub>fs</sub> = Pressure increase